



**XCELTHERM® PG FOOD GRADE
SAFETY DATA SHEET**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

XCELTHERM® PG Food Grade
ISO 9001:2008 Certification Number: C2015-00068

Recommended Use

Used in antifreeze and deicing applications.

Company Identification

Headquarters and Manufacturing Facility
Radco Industries, Inc.
700 Kingsland Drive
Batavia, IL 60510

Manufacturing Facility
Radco Industries, Inc.
39W930 Midan Drive
LaFox, IL 60147

Customer information number: 1-630-232-7966

EMERGENCY TELEPHONE NUMBER

Advisory Office in case of poisoning: Chemtrec

Chemtrec (North America): 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification of mixture:

Food Grade Propylene glycol is generally recognized as safe by the Food and Drug Administration.

Hazard Pictograms: None

Signal Word: None

Hazard Statements:

H317: May cause an allergic skin reaction

H335: May cause respiratory irritation.

Precautionary Statements:

P101: If medical advice is needed, have product container or label at hand.

P305 + P341 + P351: IF IN EYES: Rinse cautiously with water for several minutes. If irritation persists, get medical attention.

P303 + P350: IF ON SKIN (or hair): Gently wash with soap and water.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

3. COMPOSITION/INFORMATION ON INGREDIENTS



Components	%Content	CAS Number
Propylene glycol, food grade USP	>90%	57-55-6
Additive package	< 10%	Proprietary

4. FIRST-AID MEASURES

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation or other effects persist, immediately call a doctor.

Ingestion

Expected to be harmless if ingested.

Inhalation

Move to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. Remove from further exposure. Immediately call a doctor.

Skin

Wash exposed skin with soap and water.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

For small fires use carbon dioxide, dry chemical or foam.
For large fires use alcohol-type foam, universal type foam or water fog.

Fire-Fighting Equipment

Firefighter should wear normal protective equipment (full bunker gear) and positive-pressure contained breathing apparatus. Water can be used to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can cause environmental damage. Dike and collect water used to fight fires.

Special Fire-Fighting Procedures

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, isolate for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

6. ACCIDENTAL RELEASE MEASURES

Wear protective clothing when taking up spill. Eliminate sources of ignition. This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains. Should this product enter sewers or drains, it should be pumped out into an open vessel.

7. HANDLING AND STORAGE

Handling

Do not breathe vapors/dust. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Storage

Do not store in open or unlabeled containers. Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

WEEL (particulate): 10 mg/m³



Respiratory Protection

Use with adequate ventilation. Avoid breathing vapor. If heated and ventilation is inadequate, use NIOSH certified respirator, which will protect against organic vapor.

Hand Protection

Wear clothing and gloves that cannot be penetrated by chemicals or oil.

Eye Protection

Safety glasses, chemical goggles, or face shields recommended to prevent contact.

Other Protection

Do not eat, drink, or smoke when handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear, colorless liquid
Odor:	Faint
Odor threshold:	Not available
Auto-ignition temperature:	> 371°C (700°F)
Decomposition temperature:	Not available
Evaporation Rate (n-butyl acetate = 1):	< 1
Flash point Cleveland Open Cup (ASTM D92):	Not available
Flash point Pensky-Martens (ASTM D93):	> 99°C (210°F)
Flammability (solid, gas):	Must be preheated
Lower flammability limit:	2.6%
Upper flammability limit:	17.4%
Normal boiling point:	> 186°C (367°F)
Melting point/freezing point:	-60°C (-76°F)
Partition coefficient (n-octanol/water), Log P _{ow} :	< 0.01
pH:	6.5
Solubility in water:	Complete
Relative density (ASTM D1298) 15.6°C/15.6°C:	1.06
Vapor density:	2.26
Vapor pressure:	0.12 mmHg at 20°C (68°F)
Viscosity (ASTM D445):	52 cSt at 20°C (68°F)
Volatile organic compounds (VOC):	28%

10. STABILITY AND REACTIVITY INFORMATION

Materials to avoid

Exposure to materials which are highly oxidizing should be avoided.

Hazardous polymerization

Does not occur.

Hazardous decomposition products

Incomplete combustion may give various cracked and oxidized hydrocarbons.



Stability

Stable

11. TOXICOLOGICAL INFORMATION

Acute toxicity and immediate effects

Eye contact

Little to no effect expected.

Eye contact

May cause mild eye irritation.

Inhalation

May cause respiratory irritation.

Ingestion

Little to no effect expected.

Chronic toxicity effects

Skin sensitization

Non-sensitizing

Reproductive effect

No known effects.

Mutagenicity

No known effects.

Carcinogenicity

No component of this product is identified as a carcinogen by NTP, IARC or OSHA.

12. ECOLOGICAL CONSIDERATIONS

Aquatic toxicity

EC50 *Daphnia*, 48 hours: >43,500 mg/L

LC50 Sheepshead minnow, 96 hour: 23,800 mg/L

Biodegradability

Readily biodegradable.

Bioaccumulation

Not expected to occur.

13. DISPOSAL INFORMATION

Disposal must be in accordance with applicable federal, state, or local regulations.

Do not allow product to reach ground water, water course, or sewage systems.

This unused material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets criteria for being toxic, corrosive, ignitable, or reactive according to U.S. EPA



definitions (40 CFR Subpart C). This material could also become hazardous waste if it is mixed with or comes into contact with a listed hazardous waste. If it is a hazardous waste, regulations in 40 CFR 262-266, 268, 270, and 279 may apply.

“Empty” containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove and even a trace of remaining material constitutes as explosive hazard. “Empty” drums should be completely drained, properly bunged, and promptly returned to a drum recycler. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

14. TRANSPORT INFORMATION

U.S. Dept. of Transportation Shipping Name

Not regulated.

Canadian Transportation of Dangerous Goods Shipping Name

Not regulated.

European Rail/Road (ADR/RID) Shipping Name

Not regulated.

Air (ICAO/IATA) Shipping Name

Not regulated.

Sea (IMO/IMDG)

Not regulated.

15. REGULATORY INFORMATION

California (Proposition 65)

This product does not contain any of the substances known to the State of California to cause cancer, birth defects, or reproductive harm.

CERCLA Reportable Quantity

This product is not reportable under 40 CFR Part 302.4.

Environmental Protection Agency

None of the ingredients are listed

National Toxicology Program (NTP)

None of the ingredients are listed.

OSHA Hazard Communication Standard

Not hazardous per 29 CFR 1910.1200(d).

SARA Title III Section 302 Extremely Hazardous Substances (40 CFR Part 355)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA Title III Sections 311/312 Hazardous Categorization (40 CFR Part 370)

Hazardous categories for this product are: Acute=no; Chronic=no; Fire=no; Pressure=no; Reactive=no.

SARA Title III Section 313 (40 CFR Part 372)

This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

U.S. Inventory (TSCA)



Listed on inventory.

Australia Inventory (AICS)

Listed on inventory.

Canada Inventory (DSL)

All of the ingredients are listed.

China (CICS)

None of the ingredients are listed.

EC Inventory (EINECS/ELINCS)

In Compliance

International Agency for Research on Cancer (IARC)

None of the ingredients are listed.

Japan Inventory (MITI)

Listed on inventory.

Korea Inventory (ECL)

Listed on inventory.

16. OTHER INFORMATION

Safety Data Sheet Creation Date: 9 July 2015

Safety Data Sheet Revision Date: 26 February 2018

The information herein is given in good faith, but no warranty, expressed or implied, is made. Consult **Radco Industries, Inc.** for further information.

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

XCEL THERM® Trademark of Radco Industries, Inc.